Diag Cht 110.1251-2
Form 504
U. S. COAST AND GEODETIC SURVEY
DEPARTMENT OF COMMERCE
DESCRIPTIVE REPORT
Type of Survey Lydrographic
Field No. Office No. 2738
0),100 110
LOCALITY
State Florida
General locality approaches
Locality to Key West
Labor
1985
CHIEF OF PARTY

LIBRARY & ARCHIVES

B-1870 1 (1)++

39 GEODET SUBVEY



JUL 10 1 42 Pm 1905

FILE: FERREI

IT IN (

Creasury Department, U. S. COAST AND GEODETIC SURVEY.

O. H. Tittmann

Superintendent.

State: Florida

DESCRIPTIVE REPORT.

Hydrographic Sheet No.2738

LOCALITY:

Approaches

Key West Harbor

190 5

CHIEF OF PARTY:

P.A. Welker, Ass't, C.& G.S.

U. S. C. & G. SURVEY, LIBRARY AND ARCHIVES,

JUL 15 1905

Acc. No.

POST-OFFICE ADDRESS: General Delivery, P.O., Baltimore, Md.

TELEGRAPH ADDRESS: Foot of Chesapeake Street "

EXPRESS OFFICE:

Bepartment of Commerce and Labor

COAST AND GEODETIC SURVEY Str. "Bache",

Baltimore, Maryland,

July 11th, 1905.

Mr. O. H. Tittmann,

といれるし をしがいさい

Superintendent, Coast and Geodetic Survey,

JUL 15 1905

Washington, D. C.

C. & G SORVEY ARCHIVES

Sir:-

In obedience to Instructions and Memoranda for Descriptive Reports, 1887, I have the honor to submit the following report on Hydrographic Sheet No. 2738.

- 2. This work consists of an hydrographic resurvey of the South East Channel, entrance to Key West Harbor, Florida.
- 3. The character of the bottom is mostly hard and irregular in contour. Numerous coral heads are to be found, and the narrow channel cannot be considered safe for vessels drawing over 16 feet of water, unless all of the dangerous spots are accurately buoyed. The shoals and coral heads rise abruptly from deep water and the lead cannot be relied upon for giving warning in approaching the same.
- 4. Owing to the strong currents sweeping around the shoals, compass courses cannot be relied upon unless corroborated by other evidence.
- 5. The system used in developing the channel was to run lines approximately parallel with its axis at a distance of from

10 to 70 metres apart. In all of the lines a drag, sweeping a width of about 10 metres and set to a depth of from three to five fathoms was used, the depth to which the drag was set varrying according to the contour of the bottom.

6. No further descriptive report is considered necessary.

Very respectfully,

P. a. Welker.

Assistant, C.& G.Survey,

Commanding.

Department of Commerce and Labor

Myd Sheet #2738

The plotting was well done and the

Af Simens

Sept 6 1905